


DIMENSIONS: SX

Wheels	X	Y
9.5 R20	322	1060
300/70 R20	322	1240
280/85 R20	341	1145
320/70 R20	334	1225
340/65 R18	300	1285
33x12.50-15	278	1240
320/70 R24	395	1240

*Height calculated with the operator of average height sitting (cm 175)



TECHNICAL DATA: SX

ERGITS



SX 7800"S"

SX 9400"S"

Chassis	"ACTIO™" – Full chassis with oscillation • Articulated • 4 equal wheel drive - Front and rear final drive							
Engine Type	Diesel direct injection with counter rotating weight system							
Emissions Regulations	Stage 3A				Stage 3A			
N° Cylinders	4 - 16 Valves				4 Turbo - Intercooler			
Displacement (CC)	3319				2970			
Power kW/HP (97/68/CE)	52/71				64/87			
Maximum engine revs	2500				2600			
Torque max (Nm/revs)	236/1600				380/1000			
Cooling	Water				Water			
Tank Capacity (litres):	50				50			
Transmission	Synchronised 32 speed gear box: 16 forward and 16 reverse with synchronised inverter							
PTO	Rear, independent and synchronised at 540/540E rpm with progressive electrohydraulic engagement							
Shaft	Profile 1" 3/8 with 6 splines with facilitated engagement							
Transmission clutch	Hydraulic control							
Drive disengagement	Electrohydraulic control on the front							
Rear hydraulic lift	With 3 point hitch cat. 1 and cat. 2 - Capacity (Kg): 2420							
Operating Pressure (bar)	160							
Steering	Hydraulic with 2 pistons							
Brakes	Standard: hydraulic front and rear disk brakes in oil bath Independent emergency and parking brake: band type on transmission							
Platform	Suspended on Silent Block							
Tyres	9.5 R20	300/70 R20	280/85 R20	320/70 R20	340/65 R18	33x12.50-15	320/70 R24	
Weight in order of speed (Kg):	With roll bar: 2165				With roll bar: 2135			
	With cab: 2255				With cab: 2225			
Standard Features	<ul style="list-style-type: none"> • Rear or front/rear differential lock with electrohydraulic control • Oscillating lifting arms with lateral stabilizers • Adjustable, suspension seat with safety belt • Foldable protection roll bar • Adjustable wheel rims • Auxiliary rear hydraulic remotes with 1 double acting distributor with floating position, 1 oil reflow (total 3 quick couplings) • Rear adjustable height tow hitch • Front tow hitch • Multifunctional digital instrument • Battery • Electrical power point • Safety starting device on the inverter and PTO 							
Optional Features	<ul style="list-style-type: none"> • Star Light cab with air conditioning system and window on the roof, suspended on Silent Blocks • Hydraulic power lift with draft and position control • Hydraulic system with 2 double acting distributors (one of which with floating position) + 1 oil reflow (6 quick couplings) • Adjustable lifting arms with quick release couplings • Pair of front/rear ballasts • Cast iron wheel flanges for 20" and 24" rear wheels • 6 front ballast weights • Front bullbar • Front lamp guards 							

The description and illustrations in this brochure are provided simply for information purposes; they are not binding and may be varied at any time without notice

ANTONIO CARRARO SPA
Via Caltana, 24
35011 Campodarsego Padova ITALY
info@antoniocarraro.it
antoniocarraro.com

COD. 4 7318 143 - 03/2012