





StarLight cab	EasyStar chassis						
							
2100÷2170	2000÷2070						
							
1795÷1860*	2195÷2260						
DIMENSIONS	<table border="1"> <tr> <td style="text-align: center;">720÷870</td> <td style="text-align: center;">1595</td> <td style="text-align: center;">980</td> </tr> <tr> <td colspan="3" style="text-align: center;">3295÷3445</td> </tr> </table>	720÷870	1595	980	3295÷3445		
720÷870	1595	980					
3295÷3445							
*Height calculated with the operator of average height sitting (cm 175)							

TECHNICAL DATA: TRX 6500

THE **ERGIT** SERIES



Chassis	"ACTIO™" – Full chassis with oscillation • Reversibility RGS™ • Steering wheels • 4 equal wheel drive • Front and rear final drive						
Engine Type	Diesel indirect injection with counter rotating weight system Emissions Regulations: Stage 3A Displacement (CC): 2216 Maximum engine revs: 2600 Cooling: Water						
	N° Cylinders: 4 Turbo		Power kW/HP (97/68/CE): 41,5/57				Torque max (Nm/revs): 185/1800
	Tank Capacity (litres): 50						
Transmission	Synchronised 32 speed gear box: 16 forward and 16 reverse with synchronised inverter						
PTO	Rear, independent and synchronised at 540/540E rpm with progressive electrohydraulic engagement						
Shaft	Profile 1" 3/8 with 6 splines with facilitated engagement						
Transmission clutch	Hydraulic control, without the need for adjustment						
Drive disengagement	Electrohydraulic control on the front						
Rear hydraulic lift	With 3 point hitch cat. 1 - Capacity (Kg): 2100						
Operating Pressure (bar)	160						
Steering	Hydraulic with 2 pistons						
Brakes	Standard: hydraulic front and rear disk brakes in oil bath, rear steering brakes Independent emergency and parking brake: band type on transmission						
Platform	Suspended on Silent Block						
Tyres	250/80 R18	300/80-15.3	320/65 R18	300/70 R20	280/70 R18	340/65 R18	31x15.50-15
Min. ext. width (mm)	1380	1445	1460	1410	1420	1485	1690
Ground clearance (mm)	275	275	275	310	275	285	240
Weight in order of speed (Kg):	With roll bar: 2000		With chassis: 2110		With cab: 2190		
Standard Features	<ul style="list-style-type: none"> • Reversible control tower • Rear or front/rear differential lock with electrohydraulic control • Fixed lifting arms • Adjustable, suspension seat with safety belt • Protection roll bar • Adjustable wheel rims • Auxiliary rear hydraulic remotes with 1 double acting distributor with floating position, 1 oil reflow (total 3 quick couplings) • Rear adjustable height tow hitch • Front tow hitch • Multifunctional digital instrument • Battery • Electrical power point • Safety starting device on the inverter and PTO 						
Optional Features	<ul style="list-style-type: none"> • Star Light cab with air conditioning system and window on the roof, suspended on Silent Blocks • EasyStar safety chassis with 6 uprights, fitted on Silent-block, with roof and left rear view mirror, (optional) front and rear windscreens complete with wipers and right rear view mirror • Lift and hydraulic quick couplers controlled by double speed "ON/OFF" Joystick • Rear power lift with suspension (2+2 pistons) • Hydraulic power lift with draft and position control • Front power lift • Hydraulic third hitch and vertical tie-rod • Adjustable lifting arms with quick release couplings • Pneumatic seat • Slider tow hitch • Pair of front/rear ballasts • Cast iron wheel flanges for 20" rear wheels • Front bullbar 						

The description and illustrations in this brochure are provided simply for information purposes; they are not binding and may be varied at any time without notice.

ANTONIO CARRARO SPA
Via Caltana, 24
35011 Campodarsego Padova ITALY
info@antoniocarraro.it
antoniocarraro.com

COD. 4 7318 137 - 06/2012